

EXTRUDABLE FLUOROPOLYMER BLENDS

Technical Field

5 This invention relates to melt processable fluorothermoplastic compositions comprising a blend of different fluoropolymers, as well as methods of improving extrusion properties in extruded fluorothermoplastics.

Background

10 Fluoropolymers have found wide utility in a vast array of applications. However, they are often beset by processing difficulties. Specific difficulties include surface roughness such as melt fracture and other problems such as die drooling.

 Higher processing temperatures can reduce some of these problems, but may involve other problems. One such problem is the molecular weight degradation of the fluoropolymer.

15 This can result in reduced physical properties, can contribute to the die drool, and the corrosive by-products can lead to premature wear of the processing equipment.

 Another alternative to reduce the surface roughness of extrudates is to reduce the processing rate. This increases the residence time of the fluoropolymer in an extruder, which also contributes to degradation. Reducing production rates is also economically undesirable.

20 Decreasing the molecular weight of the input fluoropolymer can allow for limited improvements in output, but this also decreases the mechanical properties of the polymer. Such a mechanical property detriment may then be partially offset by the addition of costly comonomers, but this modification can add production complications and detract from other physical properties.

25 Another approach toward reducing surface defects in fluoropolymers has been to create a mixture of several fluoropolymers having similar composition yet of significantly different molecular weights in attempt to balance the polymer properties with the processing parameters. In theory, a lower molecular weight portion allows for higher output rate with the blend, while a higher molecular weight portion improves the mechanical properties of the blend. This
30 compromise achieves limited success and increases the complexity required to produce such a material.

Yet another approach involved adding a polyolefin to specific fluoropolymers. However, the temperatures necessary for processing fluoropolymers are usually too high for this approach. In addition, such a material can negatively affect properties of the fluoropolymer, such as color, permeation rate, and chemical resistance.

JP 60-23701 describes a blend of a fluorinated elastomer and a copolymer of tetrafluoroethylene and hexafluoropropene (FEP) to achieve heat stress-crack resistance. U.S. Patent No. 5,051,479 describes a melt-processable thermoplastic consisting essentially of a blend of a fluoropolymer and an elastomeric tetrafluoroethylene-perfluoro(alkyl vinyl) ether copolymer.

Summary

Despite these attempts, there is still a great need to be able to process fluoropolymer materials at higher output rates while maintaining a quality finish on the part and without sacrificing mechanical properties.

Accordingly, the present invention provides a melt processable fluorothermoplastic composition comprising a major amount of a first semi-crystalline fluorinated copolymer and a minor amount of a second fluoropolymer effective to reduce melt defects in the composition. Each fluoropolymer is selected from four classes. The first class, (a), includes a semi-crystalline perfluorinated copolymer. The second class, (b), includes a fluoropolymer derived from interpolymerized units of at least one essentially perfluorinated monomer and at least one non-fluorinated hydrogen-containing monomer. The third class, (c), includes a fluoropolymer derived from interpolymerized units of at least one partially-fluorinated monomer, and optionally at least one essentially perfluorinated monomer. The fourth class, (d), includes an amorphous copolymer of tetrafluoroethylene and hexafluoropropylene. When the first fluoropolymer is selected from (a), the second fluoropolymer is a semi-crystalline fluoropolymer selected from (b) and/or (c). When the first fluoropolymer is selected from (b), the second fluoropolymer is selected from (a), (c), and/or (d). When the first fluoropolymer is a copolymer selected from (c), the second fluoropolymer is selected from (a), (b), and/or (d).

In another aspect, the present invention provides a melt processable fluorothermoplastic composition comprising a major amount of a semi-crystalline fluorinated copolymer and a minor amount of a fluoropolymer effective to reduce melt defects (such as melt fracture or surface roughness) in the composition. The second fluoropolymer (minor amount) is selected from an amorphous fluorinated copolymer derived from interpolymerized units of a perfluoro

(alkoxy vinyl) ether and a comonomer which may be partially or fully fluorinated, and/or an amorphous fluorinated copolymer derived from interpolymerized units of at least 3 mole percent (mol%) of an hydrogen containing comonomer, and a perfluoro (alkoxy vinyl) ether and/or a perfluoro (alkyl vinyl) ether. This group of materials may also be used in conjunction with the other minor component fluoropolymers as defined herein.

In another aspect, the present invention provides a method of improving extrusion properties in an extrudate. This method comprises blending a major amount of a first semi-crystalline fluorinated copolymer and a minor amount of a second fluoropolymer effective to improve extrusion properties in the composition, and melt processing the blend to form the extrudate. In this method, each fluoropolymer is selected from one of four classes: (i) a semi-crystalline perfluorinated copolymer; (ii) a fluoropolymer derived from interpolymerized units of at least one essentially perfluorinated monomer and at least one non-fluorinated hydrogen-containing monomer; (iii) a fluoropolymer derived from interpolymerized units of at least one partially-fluorinated monomer, and optionally at least one essentially perfluorinated monomer; and/or (iv) an amorphous fluorinated copolymer derived from interpolymerized units of a perfluoro (alkoxy vinyl) ether and a comonomer which may be partially or fully fluorinated, and/or an amorphous fluorinated copolymer derived from interpolymerized units of at least 3 mole percent (mol%) of an hydrogen containing comonomer, and a perfluoro (alkoxy vinyl) ether and/or a perfluoro (alkyl vinyl) ether. Also in this method, when the first fluoropolymer is selected from (i), the second fluoropolymer is a fluoropolymer selected from at least one material of class (ii), a semi-crystalline material of class (iii), and/or a material from class (iv); when the first fluoropolymer is selected from (ii), the second fluoropolymer is selected from (i), (iii), and/or (iv); and when the first fluoropolymer is a copolymer selected from (iii), the second fluoropolymer is selected from (i), (ii), and/or (iv).

When a fluoropolymer is melt-processed, issues of surface defects, output rates, and mechanical properties must be addressed. Surprisingly, when these same fluoropolymers are used in blends of the present invention, remarkably improved processing flexibility results. The extrudable compositions of the invention are not as prone to the thermal instability issues of known blends. In addition, the end-use properties of articles made from the major component fluoropolymer, such as permeation, extraction, and chemical resistance, can be preserved in the fluoropolymer blends of the present invention.

Detailed Description

In one aspect of the present invention, a fluoropolymer blend is comprised of combinations of fluoropolymers selected from four distinct classes. Materials are selected from at least two different classes to form the fluoropolymer blend of the invention.

5 The fluoropolymers and fluoropolymer blends of the invention are melt processable. As used herein, "melt processable" means that the material can be repeatedly processed with the assistance of heat. That is, the fluoropolymers and fluoropolymer blends can be extruded without thermosetting or cross-linking.

10 The fluoropolymers of the invention preferably have a melt flow index (MFI) of about 1g per 10 min or greater, under a load of 5 kg at the temperature at which they are to be processed. In general, the fluoropolymers will have a melt viscosity of less than about 10^6 Poise at the desired processing temperature. In addition, the molecular weight of the fluoropolymer is sufficiently high so as not to be considered oligomeric, *i.e.*, a number average molecular weight above about 10,000 g/mol.

15 The fluoropolymers in the blend of the invention are selected from four classes. The first class comprises monomers that are essentially perfluorinated. As used herein, "essentially perfluorinated" means that less than about 5 weight percent (wt%), more preferably less than about 1 wt% or even 0 wt%, of the monomers have hydrogen substituents. The other two classes of fluoropolymer in the blend of the invention are partially fluorinated. These
20 fluoropolymer contain interpolymerized units of hydrogen containing monomers. The constituent fluoropolymers will now be described more particularly.

The first class of fluoropolymers contains interpolymerized units of tetrafluoroethylene (TFE) and at least one other essentially perfluorinated monomer of the general formula (I):





25 $\text{CF}_2=\text{CFR}$, wherein R is R_f , R_fX , $\text{R}_f'\text{X}$ or Cl ; wherein X is F, Cl, Br, or H, R_f is a perfluorinated alkane, and R_f' is: $\text{O}(\text{R}_f^2\text{O})_a(\text{R}_f^3\text{O})_b\text{R}_f^4$ where R_f^2 and R_f^3 are the same or are different linear or branched C_1 - C_6 perfluoroalkylene groups; a and b are, independently, 0 or an integer from 1 to 10; and R_f^4 is a C_1 - C_6 perfluoroalkyl group. Examples of the monomers of this formula include hexafluoropropylene (HFP), chlorotrifluoroethylene (CTFE), perfluoroalkyl vinyl ethers (PAVE), and the perfluoroalkoxy vinyl ethers (PAOVE). Examples of the perfluoroalkyl vinyl
30 ethers include perfluoromethyl vinyl ether (PMVE), perfluoroethyl vinyl ether (PEVE), perfluoropropyl vinyl ether (PPVE), and the like, some of which are shown below.



PMVE



PEVE



Combinations of perfluoroalkyl vinyl ethers and perfluoroalkoxy vinyl ethers may also be used.

The amount of essentially perfluorinated comonomer present with the TFE in the fully fluorinated polymer is limited to the amounts that allow it to be melt processable and remain a semi-crystalline material. Typically this will range between about 2% and 30% by weight depending on the comonomer chosen and the desired properties of the fluoropolymer. In addition, these materials may be treated with fluorine to further improve their thermal stability by known methods.

The second and third classes of fluoropolymers useful in preparation of the invention are referred to as partially fluorinated fluoropolymers, for they contain some constituent hydrogen atoms. Specifically, these fluoropolymers contain interpolymerized units derived from at least one monomer that contains hydrogen. These two classes of partially fluorinated fluoropolymers are distinguished from one another by the type of constituent hydrogen containing interpolymerized units. The monomers used to make the fluoropolymer in the first of these classes contain both non-fluorinated hydrogen-containing monomers and essentially perfluorinated monomers. The monomers used to make the fluoropolymer in the second of these classes include both hydrogen and fluorine.

The second class of fluoropolymers useful in forming the blend of the present invention comprises interpolymerized units of non-fluorine containing monomers. Such non-fluorine containing monomers useful for copolymerizing with a fluorine containing monomer include ethylene, propylene, and higher alkenes and dienes. These non-fluorine-containing monomers are typically present at a level of at least 5% and are copolymerized with TFE, HFP, and/or combinations of other monomers from Formula 1. These materials may be either semi-crystalline or amorphous. In addition they may also contain minor amounts of partially fluorinated monomers, such as vinylidene fluoride (VF2). Typically such monomers are present at a level of less than about 15% by weight, preferably less than about 10% or even about 5%.

In many instances, these polymers are essentially free of partially fluorinated hydrogen containing monomers, and contain less than 1 wt% or even 0 wt% of these monomers. In particular these monomers may be free of those partially fluorinated hydrogen containing monomers which may detract from the base resistance of the polymer. In other instances, certain specific partially fluorinated monomers, such as perfluorobutyl-ethylene (PFBE), which do not significantly detract from the chemical resistance of the fluoropolymer readily may be used.

The third class of fluoropolymers useful in forming the blend of the present invention is also partially-fluorinated, hydrogen-containing fluoropolymers. These fluoropolymers contain at least 5% by weight of at least one partially fluorinated monomer that contains both hydrogen and fluorine atoms. Suitable monomers include primarily vinylidene fluoride, but also may include vinyl fluoride, and/or tri-fluoroethylene. This third class of copolymers is comprised of either homopolymers of these partially fluorinated monomers or copolymers of these monomers with TFE, HFP, and/or monomers of Formula I. They may also contain below about 5 wt% of other non-fluorinated monomers. This third class of fluoropolymers sometimes has been characterized in the art as having decreased chemical resistance to bases in comparison to the other described groups and may be more prone to dissolution or swelling by hydrocarbon solvents.

The fourth class of fluoropolymers useful in forming the blend of the present invention comprises amorphous copolymers of TFE and HFP.

The melt processable fluoropolymer blend of the invention is formed by blending two or more fluoropolymers selected from at least two of the four above-described groups of fluoropolymers. The first blend component is present in a major amount, *i.e.*, at least about 90 weight percent (wt%), more preferably at least about 95 wt% and often 98 wt% or greater, based on the total blend. This first blend component is chosen for its inherent mechanical or physical properties for a desired application and it imparts these properties to the extrudate. This first blend component is semicrystalline, *i.e.*, it has a discernible melting peak. The major component often is comprised of only one polymer, but it may also comprise two or more fluoropolymer materials that are preferably selected from the same group of fluoropolymers. If two or more fluoropolymers comprise the major component, they should have sufficient compatibility such that they do not significantly phase-separate during extrusion.

Intermediate blends may be produced to contain as low as 90%, 80%, or even 50% of the major component with the minor component making up the difference. These blends may also provide utility in the process of the invention.

The second blend component, which constitutes the minor portion of the fluoropolymer blend, is chosen from one or both of the remaining classes of fluoropolymers that were not selected as the first blend component. This minor blend component may also comprise two or more fluoropolymers selected from one, or both, of the remaining classes. The second blend component normally has a minimal effect, or no apparent effect on the mechanical properties of the extrudate or the finished article in the intended application. It aids the extrusion properties and improves the final surface characteristics of the extrudate. This second blend component is preferably melt-processable at the desired processing conditions of the first blend component.

Typically the minor component is present at a level of less than 5% by weight of the fluoropolymer blend, preferably less than 2%. In many instances, the level of this second component can be much less than 5%, such as 1% or lower, and still provide the significant benefits of the invention. In some aspects, levels of 0.5% or even 0.05% can provide benefits over the major blend component alone.

One helpful criterion for the selection of the minor component is that it should be largely immiscible with the first component. By selecting the minor component from one of the remaining groups of fluoropolymers, other than that chosen from for the major component, this immiscibility may be achieved. A simple test for determining immiscibility involves preparing a blend of the two materials at a temperature above the melting point, or above the melt processing temperature, of either material. At sufficiently high levels of the minor component, the blend component visually will appear more opaque, milky, or cloudy in comparison to either of the individual components. Amounts of the minor component necessary to achieve this affect typically vary from below about 1% up to about 5% by weight based on the total weight of the major and minor components. At lower levels of the minor component, or if the two dissimilar fluoropolymers of the blend have a similar refractive index, this effect may be unnoticed. However, the minor component will remain immiscible and may be detected by known optical microscopy methods.

The immiscibility between the major and minor components of the blend is attributed to the difference in interpolymers in the individual polymeric components of the polymer blend. For example, one component may lack a specific monomer that is appreciably present in the other component. These differentiating monomers may be either randomly dispersed

throughout the component polymer, or alternatively they may be more concentrated in certain portions of the polymer such as in a block co-polymer or a core-shell type polymer. Typically this monomeric difference will be in the presence or lack of one of the two types of hydrogen containing monomers.

5 In addition, the fluoropolymer utilized in either component may contain other monomers that augment the immiscibility between the two components. Examples of this include longer chain monomers, which impart side chains when polymerized, or those that impart chemical functionality or may serve to make the polymer chain more polarizable. Examples include, those of Formula I, wherein R_f contains at least one carbon atom and preferably at least one
10 oxygen atom. Other possibilities include both fluorinated and/or hydrogenated monomers that contain cyclic or aromatic structures, those substituted with other hetero-atoms, and monomers with chemically-functional groups. It is possible for both components of the fluoropolymer blend to contain some of the same types of monomers, provided that they do not have the adverse effect of making the two polymers compatible or miscible. The more highly modified
15 material typically should be the minor component of the blend.

In addition to its immiscibility, the minor component will typically have a viscosity that is similar to that of the major component at the intended processing conditions of the blend. The minor component may be comprised of two or more fluoropolymers of significantly different molecular weight and/or composition, and may or may not be miscible with one another. The
20 combination of the minor components remains immiscible with the major component of the blend. In addition, the minor component will be of appreciable molecular weight such that it does not easily migrate or is not easily extracted from a finished article of the blend. Minor components that are semi-crystalline or are insoluble in common hydrocarbon solvents can also serve to minimize the extractability.

25 The monomeric composition of the minor component may also be chosen to minimize its influence on the physical properties of the major component. For instance if the fluoropolymer blend is used for electrical insulation, the use of monomers which increase the dielectric constant or dissipation factor should be minimized.

The fluoropolymers used in the formation of the blend will contain at least 30% fluorine
30 by weight and preferably will contain 40% or more. The percent fluorine will also depend on whether the particular fluoropolymer is used as the major or minor component and the intended end use application for the blend. That is, many major component fluoropolymers should contain at least about 60% fluorine and some will contain 70% or more. In one aspect where the

end-use application of the fluoropolymer is wire coating for high speed data transfer, the major component could be an essentially perfluorinated material such as FEP, which can contain up to 76% fluorine by weight. Another example for the major component would be a copolymer of TFE, VF2 and HFP, which contains about 70% fluorine or more, for use as for a flexible fuel
5 hose barrier. In either case, the minor component used to form the blend could be, for example, a hydrogen-containing fluoropolymer comprising interpolymerized units of ethylene or propylene that contains about 65% to 60% or less of fluorine, or alternatively the minor phase may be an essentially perfluorinated amorphous copolymer of TFE and MV-31.

The major and minor blend components can be combined through any known means.

10 The minor component preferably is well dispersed within the major component of the fluoropolymer blend. The before-mentioned criteria for the selection of the minor component will aid in this dispersion, as will the incorporation and mixing technique chosen to prepare the blend. To effect the desired dispersion within the blend, the two components may be fed in a form such as pellet, powder, flake, or liquid dispersion, to a suitable blending or pre-blending
15 device. Typical devices for blending the materials in the molten state include single and twin screw extruders and batch mixers. In addition, more than one of these mixing techniques may be used to form the blend in which the minor component is uniformly dispersed and randomly distributed. For instance, a higher amount of the minor component, at levels up to about 20%, may first be blended into the major component using a twin screw extruder. This blend may
20 then be diluted with more of the major component using another mixing technique to form the final desired composition of the fluoropolymer. This final blending step may also be the same step that is used to form a finished extruded article. When the minor component is well dispersed, the fluoropolymer blend will enhance the performance benefits of the invention. Proper dispersion can also allow for lower use levels of the minor component.

25 When the major component of the blend is comprised of a perfluorinated polymer, the selected fluoropolymer will be copolymers of TFE and at least 2 wt% of one or more comonomers of Formula I. Preferred comonomers include HFP at levels up to about 20 wt% and/or PAVE (perfluoroalkylvinylethers) at levels of up to about 10 wt%. Copolymers of TFE and HFP are commonly referred to as FEP. Copolymers of TFE and PAVE, such as PPVE-1,
30 are referred to as PFA. Commercially available polymers useful in the is aspect of the invention include FEP 6322, PFA 6502N, PFA FLEX X 6515 UHP from Dyneon LLC (Oakdale, MN); FEP 5100, PFA 950 HP and FEP CJ95 from DuPont (Wilmington, DE), FEP NP101 and PFA 238SH from Daikin (Japan) and MFA 620 from Ausimont (Italy).

The minor component that is blended with the major component perfluorinated polymer will also be semi-crystalline. It is selected from either group of partially fluorinated fluoropolymers. Alternatively, it may be a polymer comprising any combination of the two different types of hydrogen containing monomers with other fluorinated polymers. Examples include ethylene-tetrafluoroethylene (ETFE), hexafluoropropylene-ethylene-tetrafluoroethylene (HTE), tetrafluoroethylene-propylene (TFE/P), poly (vinylidene fluoride) (PVdF), and tetrafluoroethylene-hexafluoropropylene-vinylidene fluoride (THV).

When the major component is chosen from the group of fluoropolymers that contain interpolymerized units lacking fluorine along with fluorinated monomers, the preferred materials are copolymers which contain both ethylene and TFE. Preferably the ethylene content is at least about 10 wt%. Additionally, these polymers may contain HFP, perfluoroalkylvinylethers, and other long chain monomers such as PFBE. Commercially available materials of these preferred polymers include ETFE 6235, ETFE 6235J, HTE X 1510 and HTE X 1705 from Dyneon and EFEP from Daikin.

The minor component for this blend can be selected from either the group of fully fluorinated copolymers or from the group of partially fluorinated polymers that are comprised of monomers which contain both fluorine and hydrogen. Examples of this latter group include homopolymers and copolymers of VF₂ with monomers of Formula I. A group of preferred materials for the minor component are those that contain substantially lower levels of hydrogen containing monomers than does the major blend component. Examples of this group include copolymers of TFE with HFP and/or PPVE.

When the major blend component is selected from the group comprised of monomers that contain both hydrogen and fluorine, the fluoropolymer will be a copolymer of VF₂ and at least one other copolymerizable comonomer. The preferred materials will contain at least 5 wt% and preferably 10 wt% and higher of essentially perfluorinated monomers. Preferred monomers include TFE and HFP, but may also contain smaller amounts of monomers from Formula I, such as PPVE. In many instances, the levels of VF₂ in the major component may be as low as 15 wt% or 10 wt%, and in some aspects as low as 5 wt%. Commercially available polymers useful in this aspect of the invention include THV 200, THV500, and THV815 from Dyneon.

The minor component for this blend is chosen from either the group of perfluorinated fluoropolymers or those formed from copolymers of fluorine free monomers with fluorine containing monomers. A group of preferred materials for the minor component in this blend are those that contain substantially different levels of hydrogen containing monomers than does the

major component. Examples of this group include copolymers of TFE with HFP and/or a PAVE such as PPVE.

A preferred group of fluoropolymers, that is particularly well suited for use as the minor component in the formation of a blend of the invention (with any major component), are those copolymers which contain higher levels of perfluoroalkylvinylether or perfluoroalkoxyvinylether monomers and at least one copolymerizable comonomer. This group may be considered as a subset of any of the before mentioned classes of fluoropolymers, but it is not limited to being semi-crystalline. Typically the level of these specific monomers will be such that the fluoropolymer is nearly or completely amorphous and lack a discernable or appreciable melting point as determined by DSC (differential scanning calorimetry). The relatively high amounts of these monomers in the minor component fluoropolymer contributes to the immiscibility required of the blend.

Preferred comonomers for forming this class of minor component that are rich in PAVEs and/or PAOVEs include primarily TFE and VF2. Preferably, the fluoropolymer will contain at least 3 mole percent (mol%), more preferably at least about 5 mol%, of VF2 or other hydrogen containing monomers. When there is less than 3 mol% of VF2, the fluoropolymer will contain a perfluoro alkoxy vinyl ether monomer.

The uniqueness of this group of fluoropolymers allows them to be used as the minor component to form a fluoropolymer blend with any of the before mentioned semi-crystalline, melt processable fluoropolymers, provided that the two components remain immiscible. Specific examples include FEP as the major component and copolymers of TFE and MV-31 as the minor and THV as the major and copolymers of VF2 and PMVE as the minor blend component. In addition, other minor component fluoropolymers as defined herein may be used in conjunction with these PAVE/ PAOVE materials.

Additives such as pigments, fillers, conductive agents and inorganic materials are often added to modify the properties of fluoropolymers. The ability to incorporate these materials and to achieve good dispersion and distribution of them throughout the fluoropolymer matrix can be difficult. Interactions between the fluoropolymer and the additive can lead to reactions that may degrade either component. These interactions can also cause substantial decreases in the MFI (increasing melt viscosity) of the resulting compound, which further hinders its processability. In addition, this rise in viscosity can lead to overheating of the compound during processing that can lead to further degradation of the fluoropolymer.

It has now been found that the addition of a minor blend component along with the additive to the major blend component can substantially mitigate the interactions between the additive and the major blend component. The fluoropolymer blends of the invention may also serve to improve the dispersion of additives that are otherwise difficult to incorporate into the major blend component. In general, the fluoropolymers that are chosen as the minor blend component to improve the dispersion of the additive are from the same previously described classes of fluoropolymers and the same teachings for selection of the major and minor component apply.

One or more additive(s) may be incorporated into the fluoropolymer blend via any known means. For example, the additive may be pre-blended into the minor component and this mixture subsequently can be added to the major component. Alternatively, the additive(s) and minor component(s) together can be added to the major component(s) using one blending procedure. When the additive is pre-blended into the minor component, the amount of minor component in the final fluoropolymer blend may be as high as 20% by weight or higher.

In one embodiment the viscosity of the minor component may be significantly lower than that of the major component to aid the incorporation of the additive. This difference in viscosity between the two fluoropolymer components may be an order of magnitude or greater, or even two orders of magnitude or greater.

In another embodiment, the minor component is chosen such that it has less of an interaction or interference with the additive than the major component. This embodiment of the invention helps incorporate an additive into the major blend component. An easy test to determine if a fluoropolymer is less interfering than another is to make a simple melt compound of the additive and the fluoropolymer and compare it to the compound of another fluoropolymer with the additive. The interactions that may occur include discoloration, off gassing, and changes in viscosity. Examples of reactive fluoropolymers are those which comprise partially fluorinated monomers.

While the minor component may aid in the process of dispersing the additive, the other benefits it provides to the fluoropolymer blend may be diminished by the presence of the additive in some embodiments. Means to minimize or even overcome this effect may be as simple as increasing the amount of the minor component fluoropolymer in the blend. An alternative is to provide an additional minor component to the blend. In this embodiment, one of the minor component fluoropolymers may serve primarily to improve the dispersion of the additive, while the other aids in the processing of the major component. The minor component

that is intended for improving the processing of the overall blend can be added as the final ingredient after pre-blending the other components to minimize any adverse interactions with the rest of the mixture.

The blends of the invention can provide a variety of improvements to the extrusion process. In comparison to the extrusion of major component by itself, the inventive fluoropolymer blend can reduce the torque, and/or pressure in an extrusion process. It may also reduce surface defects such as melt fracture and improve the surface finish of extruded articles. Further, the addition of the minor component, even at very low levels, can minimize the formation of die drool that could otherwise occur from the major component. The inventive fluoropolymer blends may also allow for the processing of the major component at conditions that are otherwise not feasible for the major component, such as at colder temperatures and/or higher shear rates, and can allow for the economical processing of higher molecular weight major components to gain their benefits. The invention may also provide for improved control of the extrudate dimensions, such as caliper of wire coatings. Any of these listed benefits may occur either singly or in combination with others.

Depending on the selection and usage levels of the materials used to form the fluoropolymer blend, the benefits described above may occur almost instantaneously or more slowly over a period of time. If desired, the time for these benefits to present themselves may be lessened by using a higher concentration of the minor component at the outset of the extrusion process. This initial procedure may then be followed by the intended concentration of the FP blend for formation of the end-use article. Alternatively, the major component may be extruded alone for a period of time to receive the benefits of the fluoropolymer blend while the effect of the minor component still lingers in the extrusion equipment.

The inventive fluoropolymer blends provide benefits to known extrusion processes. In general, a single screw extruder or other device is employed to pump the blend through a die or tool to shape the extrudate into the desired form, such as a film, sheet, rod, tube, hose, wire coating, laminates, containers, and the like. End use articles produced from extrusion processes include, *e.g.*, films, foils, hoses, wires, cables, coatings, laminates, bottles, and drums for applications such as chemical barriers, fluid transport, communications cables and chemical containment.

Examples

Materials

All monomers are reported as nominal values in weight percent. All polymers were commercially available or produced by known methods for aqueous emulsion polymerization.

5 FP (fluoropolymer) Description

- A Dyneon HTE X 1705, a semi-crystalline copolymer of 12% ethylene, 61% TFE, 27% HFP
- B Dyneon FEP 6322, a semi-crystalline copolymer of 86% TFE, 14% HFP
- C Dyneon PFA 6613N, a semi-crystalline copolymer of 96% TFE, 4% PPVE-1
- 10 D Dyneon THV 220G, a semi-crystalline copolymer of 40% TFE, 40% VF2 and 20% HFP
- E Semi-crystalline copolymer of 76% TFE, 13% VF2 and 11% HFP
- F Amorphous copolymer of 30% VF2, 14% TFE, 56% MV-31 and less than 1% of BTFE (bromotrifluoroethylene)
- 15 G Amorphous copolymer of 78% TFE, 21% propylene, less than 1% BTFE
- H Dynamar FX-9613, an amorphous copolymer of 60% VF2 and 40% HFP
- I Semi-crystalline copolymer of 88% TFE, 12% propylene
- J Dyneon ET 6235, a semi-crystalline copolymer of ethylene, TFE and PPVE-1
- K Dynamar PPA-2231, an amorphous copolymer of 60% VF2 and 40% HFP
- 20 L Amorphous copolymer of 51% TFE, 48% MV-31, less than 1% BTFE
- M Dyneon HTE X 1500, semi-crystalline copolymer of 12% ethylene, 61% TFE, 27% HFP
- N Semi-crystalline copolymer of 38% TFE, 40% VF2, 18% HFP and 4% PPVE-1

25 Example 1

A fluoropolymer blend was prepared by tumbling a pellet mixture of 2 lbs (908 g) of FP-A with 18 lbs (8.18 kg) of FP-B. The blend was then feed to a 2 inch (5.08cm) Davis Standard wire coating extruder with a mixing screw that was fitted with a GenCa 510 cross-head. The die and pin set used in the cross-head were 0.380 and 0.220 inches (9.65mm and 5.59mm) respectively. The temperatures of the extruder were set to deliver a melt temperature of 700°F (371°C) and the screw rpm's were set to give an output that would coat 7 mils (178µm) of insulation onto 20 mil (508µm) copper wire at 1500 fpm (457mpm). Within minutes after the addition of the blend, the tubular extrudate was opaque and smooth and the pressure in the extruder had decreased about 35%. In addition, there were no visible signs of die drool or phase separation from the blend. This blend was immediately followed by the extrusion of pure FP-B. When the extrudate returned to transparent, indicating that the blend had largely exited the die, it remained free of melt fracture for a period of about 10 minutes.

The melt fracture gradually reappeared over a period of about 5 more minutes and the pressure eventually returned to the previous starting value.

Comparative Example 1 (CE-1)

5 The extruder used in Example 1 was cleaned to bare metal and a sample of pure FP-B was feed at the same extrusion conditions. The extrudate exhibited severe melt fracture. At these conditions, nominal 20 mil (508 μ m) copper wire was coated to an average diameter of 34 mils (864 μ m). The resulting wire had a rough finish and subsequent analysis indicated the diameter down a 6 ft. (1.83m) length of the wire varied by about +/- 4 mils (+/- 102 μ m). The copper wire that was being coated had by itself a variation of less than +/- 0.1 mils (+/- 2.5 μ m) indicating that most of the variation in the coated wire sample was occurring within the fluoropolymer coating.

Example 2

Following the procedure of Example 1, another blend was prepared containing 5% of FP-A and 95% FP-B. The two resins were feed to the extruder and a similar effect was observed as in example 1. After the blend had exited the die, the extruder was feed with only FP-B and copper was threaded through the die and the wire coating process begun. Both the inner and outer surfaces of the extrudate were visibly free of melt fracture. The resulting wire had a nominal diameter of 34 mils (864 μ m) with a variation of about +/- 0.5 mils (12.7 μ m).

Comparative Example 2 (CE-2)

20 Wire was prepared according to CE-1, but the extruder was adjusted to deliver a melt temperature of 760°F (404°C). The outside of the extrudate was smooth and the inside had a faint frosted appearance indicating mild melt fracture. The resulting wire had a diameter variation of about +/- 1.5 mil (38 μ m).

Example 3

25 A FP blend of 5% of FP-A and 95% FP-B was melt-compounded on a Berstorff twin screw extruder and extruded into pellets. The pellets had a white, opaque appearance and optical microscopy revealed the minor component to be well dispersed and distributed within the major component fluoropolymer. A portion of this blend was feed at a ratio of 1 part by weight of the blend with 4 parts of FP-B to the wire coating extruder used in Example 1. The extruder was operated under similar conditions to that of Example 1 and within 30 minutes the extrudate of FP-B, which contained 1% of the minor component FP-A, was visibly free of melt fracture. In contrast to comparative Example 2, the resulting wire of this experiment had a smoother

finish and less diameter variation. The tensile and elongation properties of the wire were determined according to UL test method 444. Samples were tested both before and after heat aging (7days @ 232 C) and did not show any significant deviation from the sample produced in comparative example 2. This indicates that the presence of the minor component did not negatively affect the mechanical properties of the major component FP used to coat the wire.

Examples 4 through 11 and Comparative Examples 3 through 6

The following sets of experiments were conducted to show the changes in extrusion performance and/or changes in surface appearance of various fluoropolymer blends. The individual fluoropolymers utilized were in either pellet or powder form or in the form of small cubes about the size of the pellets. Fluoropolymer blends were produced by tumbling 5 wt% of a minor component along with 95 wt% of a major component and feeding the mixture to a Brabender single screw extruder equipped with a rod die. The die had a 0.1125 inch (2.9 mm) diameter orifice and was fitted with a die tip heater. Before extruding any of the blends, the major component of a given blend was first extruded by itself. The output rate and temperature settings of the extruder and die were adjusted until the major component exhibited severe sharkskin-type melt fracture. The FP blend was then extruded under the same conditions and observed for changes in extrusion pressure and torque, or for changes in the appearance of the extrudate, in comparison to the major component. In between each experiment, the major component was extruded by itself to re-establish the starting conditions. In some instances, the extruder was disassembled and cleaned.

Examples 4 through 6; see results in Table 1

Table 1

Experiment	Major	Minor	Melt temp.	% Pressure Decrease	Appearance
Ex. 4	FP-B	FP-A	371	65	smooth, milky
Ex. 5	FP-B	FP-E	371	8	smooth, clear
Ex. 6	FP-B	FP-F	371	25	clear, smooth

Example 7

A blend of 5% FP-G and 95% FP-B was extruded under the same conditions of example 4 to demonstrate the method claim of the invention. The blend had a 15% drop in extrusion

pressure compared to FP-B. The extrudate appeared free of melt fracture, but had a rough surface believed to be caused by the poor quality of dispersion in the fluoropolymer blend.

Comparative Example 3 (CE-3)

5 A blend of 5% of an amorphous copolymer of VF2 and HFP (FP-H) and 95% FP-B was extruded under the same conditions as Example 4. The extrudate was brown and full of bubbles.

Example 8

A fluoropolymer blend of 5% of FP-J and 95% of FP-C was extruded under the same conditions as Example 4, except an extrusion temperature of 360°C was used. The extrudate had a smooth surface and was less translucent than FP-C.

10 Example 9

The procedure of Example 8 was repeated except that FP-J was substituted for the minor component. About a 20% decrease in extrusion pressure occurred and the extrudate was smooth and opaque.

Comparative example 4

15 The procedure of Example 8 was repeated except that FP-K was substituted for the minor component. The extrudate was tan and contained bubbles.

Example 10

20 The procedure of Example 8 was repeated except that FP-L was substituted for the minor component and FP-D was substituted for the major component. The extrusion temperature was set at 210°C and the die tip heater was not used. The torque during extrusion was about 5% less than FP-D alone. The extrudate was melt fractured and milky in appearance.

Example 11

25 The procedure of Example 10 was repeated except that FP-M was substituted for the minor component. The torque during extrusion was about 10% less than FP-D alone. The extrudate was melt fractured and clear in appearance.

Comparative Example 5

30 The procedure of Example 10 was repeated except that FP-N was substituted for the minor component. There were no changes in torque or pressure during extrusion. The extrudate was transparent and the melt fracture appeared worse than that of FP-D when it was extruded alone.

Comparative Example 6

The procedure of comparative Example 10 was repeated except that FP-H was substituted for the minor component. There were no changes in torque or pressure during extrusion. The extrudate was opaque and exhibited melt fracture.

5

Various modifications and alterations of this invention will become apparent to those skilled in the art without departing from the scope and principles of this invention, and it should be understood that this invention is not to be unduly limited to the illustrative embodiments set forth hereinabove. All publications and patents are herein incorporated by reference to the same extent as if each individual publication or patent was specifically and individually incorporated by reference.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200